



**VENTURE
VOLT**

VOYAGER PORTABLE POWER STATION

541-797-6714 support@evpowerpac.com

TECHNICAL SPECIFICATIONS



| | | |
|--|---------------------|--|
| PART NO. | VOYAGER 120 | |
| VOYAGER PART NO. | EV-P120 | |
| SIZE | VOYAGER 120 | |
| WIDTH | 14" | |
| LENGTH | 22" | |
| HEIGHT | 9" | |
| WEIGHT | 55Lbs. | |
| MAIN INVERTER TERMINALS | VOYAGER 120 | |
| VOLTAGE | 12V | |
| DISCHARGE RATE CONTINUOUS | 80A | |
| DISCHARGE RATE MAXIMUM | 100A | |
| INVERTER MAXIMUM SIZE (NOT INCLUDED) | 1000W | |
| ROUND POWER PORTS (2) | VOYAGER 120 | |
| VOLTAGE | 12V | |
| DISCHARGE RATE | 15A | |
| USB CHARGE PORTS (4) | VOYAGER 120 | |
| VOLTAGE | 5V | |
| DISCHARGE RATE | 3.1A | |
| POWER SOURCE (BATTERY) | VOYAGER 120 | |
| VIPER POWER CELL PART NO. | V120 | |
| CHEMISTRY - LITHIUM IRON PHOSPHATE | LiFePo4 | |
| CAPACITY - AMP HOUR @ 12.8V | 120Ah | |
| CAPACITY - WATT HOURS | 1536Wh | |
| CONVERTER / CHARGER | VOYAGER 120 | |
| VIPER PORTABLE RAPID CHARGER PART NO. | EV-V120-C20A | |
| CHARGER WATTS | 600W | |
| CHARGER AC INPUT | 90-120V | |
| CHARGER DC OUTPUT VOLTAGE | 14.6V | |
| CHARGER DC OUTPUT DISCHARGE RATE | 20A | |
| PORTABLE SOLAR CHARGING | VOYAGER 120 | |
| INPUT VOLTAGE MAX. | 25V | |
| INPUT AMPERAGE MAX | 20A | |
| INPUT WATTAGE MAX | 360W | |
| PORT CONNECTION TYPE | SAE | |
| VICTRON ENERGY POWER METER MONITORING INFORMATION | | |
| 1. VOLTAGE | | 5. POWER CONSUMPTION DISPLAYED IN AMP HOURS (-) |
| 2. CURRENT DISPLAYED IN AMPS IN (+) OR OUT (-) | | 6. STATE OF CHARGE DISPLAYED AS A PERCENTAGE |
| 4. POWER DISPLAYED IN WATTS IN (+) OR OUT (-) | | 7. POWER REMAINING DISPLAYED IN HOURS |
| VICTRON ENERGY MODEL NO. BMV700 | | VOYAGER IS FACTORY SET FOR A LITHIUM PROFILE |